



Prime Consulting Engineers Pty. Ltd.

Design Report:

Heavy Duty (Square Umbrella) for 90km/hr Wind Speed

For



Ref: R-25-1346-1

Date: 29/04/2025

Amendment: -

Prepared by: JK

Checked by: BG



CONTENTS

1	Introduction and Scope:	3
1.1	Project Description	3
1.2	References	3
1.3	Notation	4
2	Design Overview	5
2.1	Geometry Data	5
2.2	Assumptions & Limitations	6
2.3	Exclusions	6
2.4	Design Parameters and Inputs	7
2.4.1	Load Cases	7
2.4.2	Load Combinations	7
3	Specifications	7
3.1	Material Properties	7
3.2	Buckling Constants	8
3.3	Member Sizes & Section Properties	10
4	Wind Analysis	11
4.1	Wind calculations	11
4.1.1	Summary	13
4.2	Wind Load Diagrams	14
4.2.1	Wind Load Ultimate (W_{min})	14
4.2.2	Wind Load Ultimate (W_{max})	15
5	Analysis	16
5.1	Results	16
5.1.1	Maximum Bending Moment in Major Axis	16
5.1.2	Maximum Bending Moment in Minor Axis	16
5.1.3	Maximum Shear	17
5.1.4	Maximum Axial Force	17
5.1.5	Maximum Reactions	18
6	Aluminium Member Design	19
7	Summary and Recommendations	20
8	Appendix A – Aluminium Design Based on AS1664.1	21
8.1	Post 82.5 x 5.2 mm	22
8.2	Arms (25 x 50 x 3.2 mm)	26
8.3	Brace (25 x 50 x 3.2 mm)	30
9	Appendix B – Technical Data Sheet	36



1 Introduction and Scope:

The report and certification are the sole property of Prime Consulting Engineers Pty. Ltd.

Prime Consulting Engineers have been engaged by Ultra Shade to carry out a structural analysis of **4.8m square** Umbrella Structures for **90km/hr** in open condition as a worse case scenario. It should be noted that the outcome of our analysis is limited to the selected items as outlined in this report.

This report shall be read in conjunction with the documents listed in the references ([Cl. 1.2](#))

1.1 Project Description

The report examines the effect of the peak gust wind that an equivalent moving average time of approximately 0.2S for **25 m/s (90 km/hr)** positioned for the worst effect, in open and closed conditions respectively, on **4.8m square** Umbrella Structures as the worst-case scenario. The relevant Australian Standards AS1170.0:2002 General principles, AS1170.1:2002 Permanent, imposed, and other actions and AS1170.2:2021 Wind actions are used. The design check is in accordance with AS1664.1 Aluminium Structures.

1.2 References

- The documents referred to in this report are as follows:
 - Report on results produced through SAP2000 V24 software & excel spreadsheets.
- The basic standards used in this report are as follows:
 - AS 1170.0:2002 – Structural Design Actions (Part 0: General principles)
 - AS 1170.1:2002 – Structural Design Actions (Part 1: Permanent, imposed, and other actions)
 - AS 1170.2:2021 – Structural Design Actions (Part 2: Wind Actions)
 - AS1664.1:1997 Aluminium Structures.
- Section Properties of Aluminium Section provided by the client.
- The program(s) used for this analysis are as follows:
 - SAP2000 V24
 - Microsoft Excel



Prime Consulting Engineers Pty. Ltd.
Email: info@primeengineers.com.au

Address: Level M 394 Lane Cove Rd
Macquarie Park NSW 2113
Phone: (02) 8964 1818

1.3 Notation

<i>AS/NZS</i>	Australian Standard/New Zealand Standard
<i>FEM/FEA</i>	Finite Element Method/Finite Element Analysis
<i>SLS</i>	Serviceability Limit State
<i>ULS</i>	Ultimate Limit State

2 Design Overview

2.1 Geometry Data



Square Heavy Duty Umbrella Dimensions

Size	A	B	C	D	E	F	G	H
2.5 m	2350	2850	2500	3550	1250	3600	1750	400
2.8 m	2300	2850	2830	4050	1415	3600	1550	400
2.9 m	2250	2850	2960	4200	1480	3600	1450	400
3.0 m	2250	2900	3060	4350	1530	3600	1350	400
3.6m	2300	2950	3670	5100	1835	3700	1050	450
4.0m	2300	3100	4000	5600	2000	4000	1100	450
4.5 m	2350	3250	4400	6200	2200	4150	900	450
4.8 m	2300	3300	4700	6600	2350	4150	700	450




Figure 1: Geometry of the square Umbrella



2.2 Assumptions & Limitations

- For forecast winds in excess of **80km/hr**, the umbrella structure should be closed.
- The structure is design for wind parameters as below:
 - Wind Region A
 - TC2
 - $M_s, M_t \text{ \& } M_d = 1$
- Shall the site conditions/wind parameters exceed prescribed design wind actions (refer to [Cl.4](#)), Prime Consulting Engineers Pty. Ltd. should be informed to determine appropriate wind classifications and amend computations accordingly.
- It is assumed that the fabric weighs **830gr/m²**.
- Aluminium alloy is to be **Alloy 6106-T6** for **post**, and **Alloy 6061 T6** for **arms** and **braces**.
- The **Post** is specified as **82.5 x 5.2 mm**, as outlined in the Heavy-Duty Umbrella Specifications.
- The **Arm** size is specified as **25 x 50 x 3.2 mm**, as per the Heavy-Duty Umbrella Specifications.
- The **Brace** size is specified as **25 x 50 x 3.2 mm**, as per the Heavy-Duty Umbrella Specifications.
- It is assumed that the umbrella is “empty under” for calculating wind loads. As per AS1170.2:2021, empty under is defined “Any goods or materials stored under the roof block less than 50% of the cross-section exposed to the wind”.

2.3 Exclusions

- Design of fabric.
- Wind actions due to tropical or severe tropical cyclonic areas.
- Snow and ice loads.
- Footing design.



2.4 Design Parameters and Inputs

2.4.1 Load Cases

1. G Permanent actions (Dead load)
2. W_u Ultimate wind action (ULS)
3. W_s Serviceability wind action (SLS)

2.4.2 Load Combinations

Strength (ULS):

1. 1.35G Permanent action only
2. $0.9G + W_u$ Permanent and wind actions
3. $1.2G + W_u$ Permanent and wind actions

Serviceability (SLS):

1. $G + W_s$ Wind service actions

3 Specifications

3.1 Material Properties

Material Properties										
6106-T6	F_{tu}	F_{ty}	F_{cy}	F_{su}	F_{sy}	F_{bu}	F_{by}	E	k_t	k_c
	235	210	210	144	120	480	337	70000	1	1.12

Material Properties										
6061-T6	F_{tu}	F_{ty}	F_{cy}	F_{su}	F_{sy}	F_{bu}	F_{by}	E	k_t	k_c
	262	241	241	165	138	551	386	70000	1	1.12



3.2 Buckling Constants

TABLE 3.3(D) BUCKLING CONSTANTS FOR ALLOY 6106-T6				
Type of member and stress	Intercept, MPa		Slope, MPa	Intersection
Compression in columns and beam flanges	B_c	234.44	D_c 1.36	C_c 70.85
Compression in flat plates	B_p	267.52	D_p 1.65	C_p 66.32
Compression in round tubes under axial end load	B_t	257.80	D_t 8.85	C_t *
Compressive bending stress in rectangular bars	B_{br}	395.01	D_{br} 3.63	C_{br} 72.46
Compressive bending stress in round tubes	B_{tb}	517.50	D_{tb} 37.34	C_{tb} 83.09
Shear stress in flat plates	B_s	153.44	D_s 0.72	C_s 87.57
Ultimate strength of flat plates in compression	<i>k₁</i>	0.35	<i>k₂</i> 2.27	
Ultimate strength of flat plates in bending	<i>k₁</i>	0.5	<i>k₂</i> 2.04	

* *C_t* shall be determined using a plot of curves of limit state stress based on elastic and inelastic buckling or by trial-and-error solution

TABLE 3.3(D) BUCKLING CONSTANTS FOR ALLOY 6061-T6				
Type of member and stress	Intercept, MPa		Slope, MPa	Intersection
Compression in columns and beam flanges	B_c	271.04	D_c 1.69	C_c 65.89



Compression in flat plates	B_p	310.11	D_p	2.06	C_p	61.60
Compression in round tubes under axial end load	B_t	297.39	D_t	10.70	C_t	*
Compressive bending stress in rectangular bars	B_{br}	459.89	D_{br}	4.57	C_{br}	67.16
Compressive bending stress in round tubes	B_{tb}	653.34	D_{tb}	50.95	C_{tb}	78.23
Shear stress in flat plates	B_s	178.29	D_s	0.90	C_s	81.24
Ultimate strength of flat plates in compression	<i>k₁</i>	0.35	<i>k₂</i>	2.27		
Ultimate strength of flat plates in bending	<i>k₁</i>	0.5	<i>k₂</i>	2.04		

* *C_t* shall be determined using a plot of curves of limit state stress based on elastic and inelastic buckling or by trial-and-error solution



3.3 Member Sizes & Section Properties

MEMBER(S)	Section	d	t	y _c	A _g	Z _x	Z _y	S _x	S _y	I _x	I _y	J	r _x	r _y
		mm	mm	mm	mm ²	mm ³	mm ³	mm ³	mm ³	mm ⁴	mm ⁴	mm ⁴	mm	mm
Post 82.5 x 5.2	D 82.5 x5.2	82.5	5.2	41.3	1262.8	22968.8	22968.8	31118.4	31118.4	947463.7	947464	1894927.5	27.4	27.4

MEMBER(S)	Section	b	d	t	y _c	A _g	Z _x	Z _y	S _x	S _y	I _x	I _y	J	r _x	r _y
		mm	mm	mm	mm	mm ²	mm ³	mm ³	mm ³	mm ³	mm ⁴	mm ⁴	mm ⁴	mm	mm
Arms	25x50x3.2	25	50	3.2	25.0	439.0	5278.0	3337.9	6785.5	4041.5	131949.8	41724.2	97109.2	17.3	9.7
Brace	25x50x3.2	25	50	3.2	25.0	439.0	5278.0	3337.9	6785.5	4041.5	131949.8	41724.2	97109.2	17.3	9.7



4 Wind Analysis

4.1 Wind calculations

Project: Ultra shade-heavy duty



PRIME CONSULTING ENGINEERS PTY. LTD

Job no. 25-1346-1

Designer: JK

Date: 30/04/2025

Amendment:

Name	Symbol	Value	Unit	Notes	Ref.
Input					
Importance level		2			Table 3.1 - Table 3.2 (AS1170.0)
Annual probability of exceedance		Temporary			Table 3.3
Regional gust wind speed		90	Km/hr		
Regional gust wind speed	V_R	25	m/s		
Wind Direction Multipliers	M_d	1			Table 3.2 (AS1170.2)
Terrain Category	TC	2			
Terrain Category Multiplier	$M_{Z,Cat}$	0.91			
Shield Multiplier	M_s	1			4.3 (AS1170.2)
Topographic Multiplier	M_t	1			4.4 (AS1170.2)
Site Wind Speed	$V_{Site,\beta}$	22.75	m/s	$V_{Site,\beta} = V_R * M_d * M_{Z,Cat} * M_s * M_t$	
Pitch	α	22.5	Deg		
Pitch	α	-	rad		
Width	B	4.8	m		
Length	D	4.8	m		
Height	Z	2.65	m		
Porosity Ratio	δ	1		ratio of solid area to total area	
Wind Pressure					
ρ_{air}	ρ	1.2	Kg/m ³		



dynamic response factor	C _{dyn}	1					
Wind Pressure	ρ*C _{fig}	0.311	Kg/m ²	ρ=0.5ρ _{air} *(V _{des,β}) ² *C _{fig} *C _{dyn}	2.4 (AS1170.2)		
WIND DIRECTION 1 (θ=0)							
External Pressure							
1. Free Roof				α=0°	D7		
Area Reduction Factor	K _a	1					
local pressure factor	K _l	1					
porous cladding reduction factor	K _p	1.00					
External Pressure Coefficient MIN	C _{P,w}	-0.3					
External Pressure Coefficient MAX	C _{P,w}	0.6					
External Pressure Coefficient MIN	C _{P,l}	-0.6					
External Pressure Coefficient MAX	C _{P,l}	0					
aerodynamic shape factor MIN	C _{fig,w}	-0.30					
aerodynamic shape factor MAX	C _{fig,w}	0.60					
aerodynamic shape factor MIN	C _{fig,l}	-0.60					
aerodynamic shape factor MAX	C _{fig,l}	0.00					
Pressure Windward MIN	P	-0.09	kPa				
Pressure Windward MAX	P	0.19	kPa				
Pressure Leeward MIN	P	-0.19	kPa				
Pressure Leeward MAX	P	0.00	kPa				
WIND DIRECTION 2 (θ=90)							
External Pressure							
4. Free Roof				α=180°	D7		
Area Reduction Factor	K _a	1					
local pressure factor	K _l	1					
porous cladding reduction factor	K _p	1.00					
External Pressure Coefficient MIN	C _{P,w}	-0.3					
External Pressure Coefficient MAX	C _{P,w}	0.4					
External Pressure Coefficient MIN	C _{P,l}	-0.4					
External Pressure Coefficient MAX	C _{P,l}	0					
aerodynamic shape factor MIN	C _{fig,w}	-0.30					
aerodynamic shape factor MAX	C _{fig,w}	0.40					
aerodynamic shape factor MIN	C _{fig,l}	-0.40					
aerodynamic shape factor MAX	C _{fig,l}	0.00					



Pressure MIN (Windward Side)	P	-0.09	kPa		
Pressure MAX (Windward Side)	P	0.12	kPa		
Pressure MIN (Leeward Side)	P	-0.12	kPa		
Pressure MAX (Leeward Side)	P	0.00	kPa		

4.1.1 Summary

WIND EXTERNAL PRESSURE	Direction1		Direction2	
	Min (Kpa)	Max (Kpa)	Min (Kpa)	Max (Kpa)
Windward	-0.093	0.186	-0.093	0.124
Leeward	-0.186	0.000	-0.124	0.000



4.2 Wind Load Diagrams

4.2.1 Wind Load Ultimate (W_{min})




Figure 2 Wind Min (KN, m)



4.2.2 Wind Load Ultimate (W_{max})




Figure 3 Wind Max



5 Analysis

5.1 Results

5.1.1 Maximum Bending Moment in Major Axis




Figure 4 Maximum Bending Moment - Major

5.1.2 Maximum Bending Moment in Minor Axis




Figure 5: Maximum Bending Moment - Minor



5.1.3 Maximum Shear




Figure 6 Maximum Shear

5.1.4 Maximum Axial Force




Figure 7 Maximum Axial Force



5.1.5 Maximum Reactions




Figure 8 Maximum Reactions (opened)

Max $F_x = 0.7$ kN
Max $F_y = 0.7$ kN
Max $F_z = 2.56$ kN
Max $M_x = 1.16$ kN.m
Max $M_y = 1.16$ kN.m



6 Aluminium Member Design

All Aluminium members passed. The summary results are tabulated below. Refer to [Appendix 'A'](#) for details.

MEMBER(S)	Section	d	t	V _x	V _y	P (Axial) Compression (-) Tension (+)	M _x	M _y
		mm	mm	kN	kN	kN	kN.m	kN.m
Post 82.5 x 5.2	D 82.5 x5.2	82.5	5.2	-0.70	0.00	0.17	2.51	0.00

MEMBER(S)	Section	b	d	t	V _x	V _y	P (Axial)	M _x	M _y
		mm	mm	mm	kN	kN	kN	kN.m	kN.m
Arms	25x50x3.2	25	50	3.2	-0.48	0.03	0.02	-0.83	0.04
Brace	25x50x3.2	25	50	3.2	0.00	0.07	-0.85	0.00	0.10



7 Summary and Recommendations

- The 4.8m square umbrella structure as specified has been analyzed with a conclusion that it has the capacity to withstand wind speeds up to and including **90km/hr**.
- For forecast winds in excess of **80km/hr** – the structure should be completely folded.
- For uplift due to 90km/hr, **300kg (3 kN)** holding down weight or **4/M12 HST3 M12 hef1, hnom = 60mm** Mechanical Anchor or alternatively HIT-HY 200-R + HIT-V-F (8.8) M12, heff = 70mm chemical anchors to concrete slab supplied by HILTI Australia is required.
- The bearing pressure of soil should be clarified prior to any construction.

Yours faithfully,
Prime Consulting Engineers Pty. Ltd.
Bijaya Giri, MEng, MIEAust, CPEng, NER, APEC, IntPE (Aus), PE Vic



Prime Consulting Engineers Pty. Ltd.
Email: info@primeengineers.com.au

Address: Level M 394 Lane Cove Rd
Macquarie Park NSW 2113
Phone: (02) 8964 1818

8 Appendix A – Aluminium Design Based on AS1664.1



8.1 Post 82.5 x 5.2 mm



Job no.

25-1346-1

Date:

30/04/2022

NAME	SYMBOL	VALUE	UNIT	NOTES	REF
D 82.5 x5.2	Post 82.5 x 5.2				
Alloy and temper	6105-T5				AS1664.1
Tension	F_{tu}	= 235	MPa	Ultimate	T3.3(A)
	F_{ty}	= 210	MPa	Yield	
Compression	F_{cy}	= 210	MPa		
Shear	F_{su}	= 144	MPa	Ultimate	
	F_{sy}	= 120	MPa	Yield	
Bearing	F_{bu}	= 480	MPa	Ultimate	
	F_{by}	= 337	MPa	Yield	
Modulus of elasticity	E	= 70000	MPa	Compressive	
	k_t	= 1.0			T3.4(B)
	k_c	= 1.1			
FEM ANALYSIS RESULTS					
Axial force	P	= 2.509902	kN	compression	
	P	= 0	kN	Tension	
In plane moment	M_x	= 2.316680	kNm		
		= 6			
Out of plane moment	M_y	= 4.223E-14	kNm		
DESIGN STRESSES					
Gross cross section area	A_g	= 1262.794	mm ²		
		= 6			
In-plane elastic section modulus	Z_x	= 22968.81	mm ³		
		= 8			
Out-of-plane elastic section mod.	Z_y	= 22968.81	mm ³		
		= 8			
Stress from axial force	f_a	= P/A_g			



		=	1.99	MPa	compression	
		=	0.00	MPa	Tension	
Stress from in-plane bending	f_{bx}	=	M_x/Z_x			
		=	100.86	MPa	compression	
Stress from out-of-plane bending	f_{by}	=	M_y/Z_y			
		=	0.00	MPa	compression	
Tension						
3.4.3 Tension in rectangular tubes						3.4.3
	ϕF_L	=	233.42	MPa		
		O				
	ϕF_L	=	247.69	MPa		
COMPRESSION						
3.4.8 Compression in columns, axial, gross section						
1. General						3.4.8.1
Unsupported length of member	L	=	3240	mm		
Effective length factor	k	=	1.00			
Radius of gyration about buckling axis (Y)	r_y	=	27.39	mm		
Radius of gyration about buckling axis (X)	r_x	=	27.39	mm		
Slenderness ratio	kLb/r_y	=	118.29			
Slenderness ratio	kL/r_x	=	118.29			
Slenderness parameter	λ	=	2.062			
	D_c^*	=	77.8			
	S_1^*	=	0.60			
	S_2^*	=	1.24			
	ϕ_{cc}	=	0.869			
Factored limit state stress	ϕF_L	=	42.90	MPa		
2. Sections not subject to torsional or torsional-flexural buckling						3.4.8.2
Largest slenderness ratio for flexural buckling	kL/r	=	118.29			
3.4.11 Uniform compression in components of columns, gross section - flat plates						
Uniform compression in components of columns, gross section - curved plates with both edges, walls of round or oval tube						3.4.11



	k_1	=	0.35			T3.3(D)
mid-thickness radius of round tubular column or maximum mid-thickness radius	R_m	=	38.65			
	t	=	5.2	mm		
Slenderness	R_m/t	=	7.432692			
Limit 1	S_1	=	0.62			
Limit 2	S_2	=	672.46			
Factored limit state stress	ϕF_L	=	210.68	MPa		
Most adverse compressive limit state stress	F_a	=	42.90	MPa		
Most adverse tensile limit state stress	F_a	=	233.42	MPa		
Most adverse compressive & Tensile capacity factor	f_a/F_a	=	0.05		PASS	
BENDING - IN-PLANE						
3.4.13 Compression in beams, extreme fibre, gross section round or oval tubes						
Unbraced length for bending	L_b	=	3240	mm		
Second moment of area (weak axis)	I_y	=	9.47E+05	mm ⁴		
Torsion modulus	J	=	1.89E+06	mm ³		
Elastic section modulus	Z	=	22968.81	mm ³		
	R_b/t	=	7.43			
Limit 1	S_1	=	42.32			
Limit 2	S_2	=	83.09			
Factored limit state stress	ϕF_L	=	233.42	MPa		3.4.13
3.4.18 Compression in components of beams - curved plates with both edges supported						
	k_1	=	0.5			T3.3(D)
	k_2	=	2.04			T3.3(D)
mid-thickness radius of round tubular column or maximum mid-thickness radius	R_b	=	38.65	mm		
	t	=	5.2	mm		
Slenderness	R_b/t	=	7.432692			
			3			



Limit 1	S_1	=	3.61		
Limit 2	S_2	=	83.09		
Factored limit state stress	ϕF_L	=	198.63 MPa		
Most adverse in-plane bending limit state stress	F_{bx}	=	198.63 MPa		
Most adverse in-plane bending capacity factor	f_{bx}/F_{bx}	=	0.51	PASS	
BENDING - OUT-OF-PLANE					
NOTE: Limit state stresses, ϕF_L are the same for out-of-plane bending (doubly symmetric section)					
Factored limit state stress	ϕF_L	=	198.63 MPa		
Most adverse out-of-plane bending limit state stress	F_{by}	=	198.63 MPa		
Most adverse out-of-plane bending capacity factor	f_{by}/F_{by}	=	0.00	PASS	
COMBINED ACTIONS					
4.1.1 Combined compression and bending					4.1.1
	F_a	=	42.90 MPa		3.4.11
	F_{ao}	=	210.68 MPa		3.4.11
	F_{bx}	=	198.63 MPa		3.4.18
	F_{by}	=	198.63 MPa		3.4.18
	f_a/F_a	=	0.046		
Check:	$f_a/F_a + f_{bx}/F_{bx} + f_{by}/F_{by} \leq 1.0$				4.1.1
i.e.	0.55	≤	1.0	PASS	
SHEAR					
3.4.24 Shear in webs (Major Axis)					3.4.24
	R	=	41.25 mm		
	t	=	5.2 mm		
Equivalent h/t	h/t	=	31.50		
Limit 1	S_1	=	29.82		
Limit 2	S_2	=	59.31		
Factored limit state stress	ϕF_L	=	112.64 MPa		



Stress From Shear force	f_{sx}	=	V/A_w			
			0.74	MPa		
3.4.25 Shear in webs (Minor Axis)						3.4.24
Clear web height	R	=	41.25	mm		
	t	=	5.2	mm		
Equivalent h/t	h/t	=	31.50			
Factored limit state stress	ϕF_L	=	112.64	MPa		
Stress From Shear force	f_{sy}	=	V/A_w			
			0.00	MPa		
Most adverse shear capacity factor (Major Axis)	f_{sx}/F_{sx}	=	0.01	MPa		
Most adverse shear capacity factor (Minor Axis)	f_{sy}/F_{sy}	=	0.00	Mpa	PASS	
COMBINED ACTIONS						
4.4 Combined Shear, Compression and bending						4.4
Check: $f_a/F_a + f_b/F_b + (f_s/F_s)^2 \leq 1.0$						
i.e. 0.55 ≤ 1.0					PASS	

8.2 Arms (25 x 50 x 3.2 mm)



Job no. 25-1346-1

Date: 30/04/2025

NAME	SYMBOL	VALUE	UNIT	NOTES	REF
25x50x3.2	Arms				
Alloy and temper	6061-T6				AS1664.1
Tension	F_{tu}	= 262	MPa	Ultimate	T3.3(A)
	F_{ty}	= 241	MPa	Yield	
Compression	F_{cy}	= 241	MPa		
Shear	F_{su}	= 165	MPa	Ultimate	
	F_{sy}	= 138	MPa	Yield	
Bearing	F_{bu}	= 551	MPa	Ultimate	
	F_{by}	= 386	MPa	Yield	



Modulus of elasticity	E	=	70000	MPa	Compressive	
	k_t	=	1			T3.4(B)
	k_c	=	1			
FEM ANALYSIS RESULTS						
Axial force	P	=	0	kN	compression	
	P	=	0.0167837	kN	Tension	
In plane moment	M_x	=	0.8290739	kNm		
Out of plane moment	M_y	=	0.0441878	kNm		
DESIGN STRESSES						
Gross cross section area	A_g	=	439.04	mm ²		
In-plane elastic section modulus	Z_x	=	5277.9916	mm ³		
Out-of-plane elastic section mod.	Z_y	=	3337.9352	mm ³		
Stress from axial force	f_a	=	P/ A_g		compression	
		=	0.00	MPa	Tension	
		=	0.04	MPa		
Stress from in-plane bending	f_{bx}	=	M_x/Z_x		compression	
		=	157.08	MPa		
Stress from out-of-plane bending	f_{by}	=	M_y/Z_y		compression	
		=	13.24	MPa		
Tension						
3.4.3 Tension in rectangular tubes						
	ϕF_L	=	228.95	MPa		
		OR				
	ϕF_L	=	222.70	MPa		
COMPRESSION						
3.4.8 Compression in columns, axial, gross section						
1. General						
Unsupported length of member	L	=	3550	mm		... 3.4.8.1
Effective length factor	k	=	1.00			
Radius of gyration about buckling axis (Y)	r_y	=	9.75	mm		
Radius of gyration about buckling axis (X)	r_x	=	17.34	mm		
Slenderness ratio	kLb/ry	=	286.71			
Slenderness ratio	kL/rx	=	204.77			



Slenderness parameter	λ	=	5.355		
	D_c^*	=	90.3		
	S_1^*	=	0.33		
	S_2^*	=	1.23		
	ϕ_{cc}	=	0.950		
Factored limit state stress	ϕF_L	=	7.98	MPa	
2. Sections not subject to torsional or torsional-flexural buckling					... 3.4.8.2
Largest slenderness ratio for flexural buckling	kL/r	=	286.71		
3.4.10 Uniform compression in components of columns, gross section - flat plates					
1. Uniform compression in components of columns, gross section - flat plates with both edges supported					... 3.4.10.1 T3.3(D)
	k_1	=	0.35		
Max. distance between toes of fillets of supporting elements for plate	b'	=	18.6		
	t	=	3.2	mm	
Slenderness	b/t	=	5.8125		
Limit 1	S_1	=	12.34		
Limit 2	S_2	=	32.87		
Factored limit state stress	ϕF_L	=	228.95	MPa	
Most adverse compressive limit state stress	F_a	=	7.98	MPa	
Most adverse tensile limit state stress	F_a	=	222.70	MPa	
Most adverse compressive & Tensile capacity factor	f_a/F_a	=	0.00		PASS
BENDING - IN-PLANE					
3.4.15 Compression in beams, extreme fibre, gross section rectangular tubes, box sections					
Unbraced length for bending	L_b	=	2795	mm	
Second moment of area (weak axis)	I_y	=	4.17E+04	mm ⁴	
Torsion modulus	J	=	9.71E+04	mm ³	
Elastic section modulus	Z	=	5277.9916	mm ³	
Slenderness	S	=	463.51		
Limit 1	S_1	=	0.39		



Limit 2	S_2	=	1695.86		
Factored limit state stress	ϕF_L	=	181.00 MPa		3.4.15(2)
3.4.17 Compression in components of beams (component under uniform compression), gross section - flat plates with both edges supported					
	k_1	=	0.5		T3.3(D)
	k_2	=	2.04		T3.3(D)
Max. distance between toes of fillets of supporting elements for plate	b'	=	18.6 mm		
	t	=	3.2 mm		
Slenderness	b/t	=	5.8125		
Limit 1	S_1	=	12.34		
Limit 2	S_2	=	46.95		
Factored limit state stress	ϕF_L	=	228.95 MPa		
Most adverse in-plane bending limit state stress	F_{bx}	=	181.00 MPa		
Most adverse in-plane bending capacity factor	f_{bx}/F_{bx}	=	0.87	PASS	
BENDING - OUT-OF-PLANE					
NOTE: Limit state stresses, ϕF_L are the same for out-of-plane bending (doubly symmetric section)					
Factored limit state stress	ϕF_L	=	181.00 MPa		
Most adverse out-of-plane bending limit state stress	F_{by}	=	181.00 MPa		
Most adverse out-of-plane bending capacity factor	f_{by}/F_{by}	=	0.07	PASS	
COMBINED ACTIONS					
4.1.1 Combined compression and bending					
	F_a	=	7.98 MPa		... 4.1.1(2)
	F_{ao}	=	228.95 MPa		... 3.4.8
	F_{bx}	=	181.00 MPa		... 3.4.10
	F_{by}	=	181.00 MPa		... 3.4.17
	f_a/F_a	=	0.000		... 3.4.17
Check:	$f_a/F_a + f_{bx}/F_{bx} + f_{by}/F_{by} \leq 1.0$... 4.1.1(3)



i.e. 0.94 ≤ 1.0				PASS	
SHEAR					
3.4.24 Shear in webs (Major Axis)					... 4.1.1(2)
Clear web height	h	=	43.6	mm	
	t	=	3.2	mm	
Slenderness	h/t	=	13.625		
Limit 1	S ₁	=	29.01		
Limit 2	S ₂	=	59.31		
Factored limit state stress	ϕF _L	=	131.10	MPa	
Stress From Shear force	f _{sx}	=	V/A _w		
			1.32	MPa	
3.4.25 Shear in webs (Minor Axis)					
Clear web height	b	=	18.6	mm	
	t	=	3.2	mm	
Slenderness	b/t	=	5.8125		
Factored limit state stress	ϕF _L	=	131.10	MPa	
Stress From Shear force	f _{sy}	=	V/A _w		
			0.07	MPa	
Most adverse shear capacity factor (Major Axis)	f _{sx} /F _{sx}	=	0.01	MPa	
Most adverse shear capacity factor (Minor Axis)	f _{sy} /F _{sy}	=	0.00	Mpa	PASS
COMBINED ACTIONS					
4.4 Combined Shear, Compression and bending					
Check: f _a /F _a + f _b /F _b + (f _s /F _s) ² ≤ 1.0					
i.e. 0.87 ≤ 1.0				PASS	

8.3 Brace (25 x 50 x 3.2 mm)



Job no. 25-1346-1

Date: 30/04/2025



NAME	SYMBOL	VALUE	UNIT	NOTES	REF
25x50x3.2	Brace				
Alloy and temper	6061-T6				AS1664.1
Tension	F_{tu}	= 262	MPa	Ultimate	T3.3(A)
	F_{ty}	= 241	MPa	Yield	
Compression	F_{cy}	= 241	MPa		
Shear	F_{su}	= 165	MPa	Ultimate	
	F_{sy}	= 138	MPa	Yield	
Bearing	F_{bu}	= 551	MPa	Ultimate	
	F_{by}	= 386	MPa	Yield	
Modulus of elasticity	E	= 70000	MPa	Compressive	
	k_t	= 1			T3.4(B)
	k_c	= 1			
FEM ANALYSIS RESULTS					
Axial force	P	= 0.853674 3	kN	compression	
	P	= 0	kN	Tension	
In plane moment	M_x	= 0	kNm		
Out of plane moment	M_y	= 0.103245 1	kNm		
DESIGN STRESSES					
Gross cross section area	A_g	= 439.04	mm ²		
In-plane elastic section modulus	Z_x	= 5277.991 6	mm ³		
Out-of-plane elastic section mod.	Z_y	= 3337.935 2	mm ³		
Stress from axial force	f_a	= P/ A_g			
		= 1.94	MPa	compression	
		= 0.00	MPa	Tension	
Stress from in-plane bending	f_{bx}	= M_x/Z_x			
		= 0.00	MPa	compression	



Stress from out-of-plane bending	f_{by}	=	M_y/Z_y			
		=	30.93	MPa	<i>compression</i>	
Tension						
3.4.3 Tension in rectangular tubes						
	ϕF_L	=	228.95	MPa		
		O				
		R				
	ϕF_L	=	222.70	MPa		
COMPRESSION						
3.4.8 Compression in columns, axial, gross section						
1. General						
						... 3.4.8.1
Unsupported length of member	L	=	1000	mm		
Effective length factor	k	=	1.00			
Radius of gyration about buckling axis (Y)	r_y	=	9.75	mm		
Radius of gyration about buckling axis (X)	r_x	=	17.34	mm		
Slenderness ratio	kLb/r_y	=	102.58			
Slenderness ratio	kL/r_x	=	57.68			
Slenderness parameter	λ	=	1.92			
	D_c^*	=	90.3			
	S_1^*	=	0.33			
	S_2^*	=	1.23			
	ϕ_{cc}	=	0.848			
Factored limit state stress	ϕF_L	=	55.69	MPa		
2. Sections not subject to torsional or torsional-flexural buckling						
						... 3.4.8.2
Largest slenderness ratio for flexural buckling	kL/r	=	102.58			
3.4.10 Uniform compression in components of columns, gross section - flat plates						
1. Uniform compression in components of columns, gross section - flat plates with both edges supported						
	k_1	=	0.35			...
Max. distance between toes of fillets of supporting elements for plate	b'	=	18.6			3.4.10.1
	t	=	3.2	mm		T3.3(D)
Slenderness	b/t	=	5.8125			
Limit 1	S_1	=	12.34			



Limit 2	S_2	=	32.87		
Factored limit state stress	ϕF_L	=	228.95	MPa	
Most adverse compressive limit state stress	F_a	=	55.69	MPa	
Most adverse tensile limit state stress	F_a	=	222.70	MPa	
Most adverse compressive & Tensile capacity factor	f_a/F_a	=	0.03		PASS
BENDING - IN-PLANE					
3.4.15 Compression in beams, extreme fibre, gross section rectangular tubes, box sections					
Unbraced length for bending	L_b	=	1000	mm	
Second moment of area (weak axis)	I_y	=	4.17E+04	mm ⁴	
Torsion modulus	J	=	9.71E+04	mm ³	
Elastic section modulus	Z	=	5277.991 6	mm ³	
Slenderness	S	=	165.83		
Limit 1	S_1	=	0.39		
Limit 2	S_2	=	1695.86		
Factored limit state stress	ϕF_L	=	200.85	MPa	3.4.15(2)
3.4.17 Compression in components of beams (component under uniform compression), gross section - flat plates with both edges supported					
	k_1	=	0.5		T3.3(D)
	k_2	=	2.04		T3.3(D)
Max. distance between toes of fillets of supporting elements for plate	b'	=	18.6	mm	
	t	=	3.2	mm	
Slenderness	b/t	=	5.8125		
Limit 1	S_1	=	12.34		
Limit 2	S_2	=	46.95		
Factored limit state stress	ϕF_L	=	228.95	MPa	
Most adverse in-plane bending limit state stress	F_{bx}	=	200.85	MPa	
Most adverse in-plane bending capacity factor	f_{bx}/F_{bx}	=	0.00		PASS



BENDING - OUT-OF-PLANE						
<i>NOTE: Limit state stresses, ϕF_L are the same for out-of-plane bending (doubly symmetric section)</i>						
Factored limit state stress	ϕF_L	=	200.85	MPa		
Most adverse out-of-plane bending limit state stress	F_{by}	=	200.85	MPa		
Most adverse out-of-plane bending capacity factor	f_{by}/F_{by}	=	0.15		PASS	
COMBINED ACTIONS						
4.1.1 Combined compression and bending						...
	F_a	=	55.69	MPa		4.1.1(2)
	F_{ao}	=	228.95	MPa		... 3.4.8
	F_{bx}	=	200.85	MPa		... 3.4.10
	F_{by}	=	200.85	MPa		... 3.4.17
	f_a/F_a	=	0.035			... 3.4.17
Check:	$f_a/F_a + f_{bx}/F_{bx} + f_{by}/F_{by} \leq 1.0$... 4.1.1
i.e.	0.19	≤	1.0		PASS	(3)
SHEAR						
3.4.24 Shear in webs (Major Axis)						...
Clear web height	h	=	43.6	mm		4.1.1(2)
	t	=	3.2	mm		
Slenderness	h/t	=	13.625			
Limit 1	S_1	=	29.01			
Limit 2	S_2	=	59.31			
Factored limit state stress	ϕF_L	=	131.10	MPa		
Stress From Shear force	f_{sx}	=	V/A_w			
			0.01	MPa		
3.4.25 Shear in webs (Minor Axis)						
Clear web height	b	=	18.6	mm		
	t	=	3.2	mm		
Slenderness	b/t	=	5.8125			




Factored limit state stress	ϕF_L	=	131.10	MPa		
Stress From Shear force	f_{sy}	=	V/A_w			
			0.19	MPa		
Most adverse shear capacity factor (Major Axis)	f_{sx}/F_{sx}	=	0.00	MPa		
Most adverse shear capacity factor (Minor Axis)	f_{sy}/F_{sy}	=	0.00	Mpa	PASS	
COMBINED ACTIONS						
4.4 Combined Shear, Compression and bending						
Check: $f_a/F_a + f_b/F_b + (f_s/F_s)^2 \leq 1.0$						
i.e. 0.19 \leq 1.0					PASS	



Prime Consulting Engineers Pty. Ltd.
Email: info@primeengineers.com.au

Address: Level M 394 Lane Cove Rd
Macquarie Park NSW 2113
Phone: (02) 8964 1818

9 Appendix B – Technical Data Sheet



A.B.N. 77 010 472 563
56 Zillmere Road, Boondall QLD
4034 P.O. Box 856, Virginia QLD
4014 Tel: (07) 3265 7288
Em: info@ultrashade.com.au

Heavy Duty Umbrella Specifications

Frame Specifications:

Post Specifications: 82.5mm x 5.2mm Round Tube 6106 T6 Aluminium

Arm Specification: 25mm x 50mm x 3.2mm 6106 T5 Aluminium

Winding Mechanism: Anti-tamper Rack and Pinion Gearbox

Materials: Aluminum Frame Components, Nylon Arm ends and Bushes, Stainless Steel Fittings

Finish: Dulux Powder Coat Range

Standard Frame Colours: White, Beige, Primrose, Green, Black Charcoal, Silver, White Birch,

Claret, Navy **Custom Colours Available on Request**

Available Base Types: Stainless Steel Bolt down or In-ground (Heavy Duty Umbrellas must be fixed to the ground)

Fabric Types:

100% Solution Dyed Acrylic Outdoor Awning Fabric

Large Colour Selection

UV Blockout UV Reflective

Water Resistant

Mould & Mildew Resistant

Fade Resistant Guarantee

Serge Ferrari Soltis Proof 502V2 Satin

Only available up to 5.0m Octagonal and 4.0m Square

Satin finish

Reinforced dirt resistance and easy clean-ability

Heat and weather protection

High UV resistance


High dimensional stability due to Precontraint® technology



UltraShade

A.B.N. 77 010 472 563
56 Zillmere Rd, Boondall QLD 4034
P.O. Box 856, Virginia QLD 4014
Tel: (07) 3265 7288 Fax: (07) 3265 7304
Em: info@ultrashade.com.au

UltraShade



Heavy Duty Umbrella

UltraShade Price List

Effective 1st July 2023

<u>OCTAGONAL</u>	Size	Coverage	Price Excluding GST	Price Including GST
CE 3.0m	3.0m Diameter	6.3 m ²	\$4,616.36	\$5,078.00
CE 3.5m	3.5m Diameter	8.7 m ²	\$4,657.27	\$5,123.00
CE 4.0m	4.0m Diameter	11.3 m ²	\$4,970.91	\$5,468.00
CE 4.5m	4.5m Diameter	14.4 m ²	\$5,291.82	\$5,821.00
CE 5.0m	5.0m Diameter	17.6 m ²	\$5,635.45	\$6,199.00
CE 5.5m	5.5m Diameter	21.4 m ²	\$6,055.45	\$6,661.00
CE 6.0m	6.0m Diameter	25.5 m ²	\$6,404.64	\$7,044.00
<u>SQUARE</u>	Size	Coverage	Price Excluding GST	Price Including GST
CE 3.0m	3.0m x 3.0m	9.0 m ²	\$4,825.45	\$5,308.00
CE 3.6m	3.6m x 3.6m	12.9 m ²	\$5,140.00	\$5,654.00
CE 4.0m	4.0m x 4.0m	16.0 m ²	\$5,455.45	\$6,001.00
CE 4.5m	4.5m x 4.5m	20.2 m ²	\$5,770.00	\$6,347.00
CE 4.8m	4.8m x 4.8m	23.0 m ²	\$6,085.45	\$6,694.00

All umbrellas include an **Acrylic Fabric Canopy** with **No Valance**.

All above prices includes the choice of either a;

Stainless Steel **Bolt Down Base** or Stainless Steel **In-ground Base**

Optional Extras


Valance (Straight or Scalloped)	\$357.27	\$393.00
Serge Ferrari 502V2 Satin Surcharge	\$283.64	\$312.00
Extra Spigot Only	\$215.45	\$237.00
Extra Bolt Down Base Only	\$215.45	\$237.00
Extra In Ground Base Only	\$215.45	\$237.00
Velcro 4 sides - 8 x panels (Square only)	\$330.91	\$364.00
Velcro per panel (Square only)	\$47.27	\$52.00
Gutter	\$330.91	\$364.00
Acrylic Dust Cover with Zip Replacement	\$610.91	\$672.00
Handle	\$70.00	\$77.00
Installation	P.O.A.	P.O.A.



Octagonal Heavy Duty Umbrella Dimensions

Size	A	B	C	D	E	F	G	H
3.5 m	2300	2850	3500	3200	1350	3650	1800	400
4.0 m	2300	2950	4000	3700	1500	3750	1650	400
4.5 m	2300	3000	4500	4150	1750	3900	1500	450
5.0 m	2400	3250	5000	4550	1900	4050	1450	450
5.5 m	2350	3200	5500	5100	2100	4100	1200	500
6.0 m	2400	3250	6000	5460	2300	4150	1050	500


NB: To be used as a guide only, all measurements are approximate






Square Heavy Duty Umbrella Dimensions

Size	A	B	C	D	E	F	G	H
2.5 m	2350	2850	2500	3550	1250	3600	1750	400
2.8 m	2300	2850	2830	4050	1415	3600	1550	400
2.9 m	2250	2850	2960	4200	1480	3600	1450	400
3.0 m	2250	2900	3060	4350	1530	3600	1350	400
3.6m	2300	2950	3670	5100	1835	3700	1050	450
4.0m	2300	3100	4000	5600	2000	4000	1100	450
4.5 m	2350	3250	4400	6200	2200	4150	900	450
4.8 m	2300	3300	4700	6600	2350	4150	700	450



UltraShade

A.B.N. 77 010 472 563
56 Zillmere Rd, Boondall QLD 4034
P.O. Box 856, Virginia QLD 4014
Tel: (07) 3265 7288 Fax: (07) 3265 7304
Em: info@ultrashade.com.au



Heavy Duty Umbrella Installation Instructions


Bolt Down Installations - Fixing to Concrete:

Supplied Parts:	Recommended Fixings:	Tools Required:
<ul style="list-style-type: none">a) The Base Plate (250mm x 250 mm x 12mm)b) Umbrella Spigotc) Five 3/8" x 1" Boltsd) Five 3/8" Spring Washerse) Two 1/2" Grub Screwsf) One 1/4 "Allen Keyg) One M8 x 90 mm Stainless Bolt & Nylock Nuth) Umbrella Hati) Umbrella Handle	<p>M12 x 100mm Dyna Bolts - Stainless Steel</p> <p>M12 Chem Set – Stainless Steel</p> <p>M12 Screw Bolt – Galvanized</p> <p>Minimum Concrete Thickness: Reinforced concrete slab 100mm thick.</p> <p>PPE Required: Dust mask, Safety Glasses, Hearing Protection, Gloves</p>	<ul style="list-style-type: none">1. M12 Concrete SDS Drill Bit2. SDS Drill3. Post Level4. Dust Extraction5. Spanner/Socket Set6. Cordless Drill7. Tape Measure8. 8mm Cobalt Drill Bit9. 9/16" Spanner10. 1 box M12 Flat Washer

1. Bolt the spigot to the base plate using the 3/8" x 1" bolts and spring washers supplied using the 9/16" spanner.
2. Slide the spigot and the attached base up inside the umbrella post and lock in place using the Allen Key with the two supplied 1/2" Grub Screws
3. Attach the Hat to the umbrella using the threaded hole at the top of the umbrella with the 9/16" Spanner. Once the Hat is attached, do not lay umbrella down as to not damage the hat.
4. Stand the umbrella in approximate location using 3 people. Have one person on the base end and two people on the canopy end, carry the umbrella to the approximate position and rest the base on the ground while two people hold the umbrella up. Have someone hold the base so it does not slip whilst two people push the umbrella vertical. Open the umbrella by removing the strap, attaching the handle and pushing all 8 arms out. Tighten the umbrella and lock in place. Have a few people hold the umbrella and measure to final position.
5. Using the post level, ensure the umbrella is plumb. Use M12 Stainless Steel Flat Washers under the fixing holes to level the base plate if required. The fixing bolts will be able to pass through the washers and hold the packing in place.
6. Use the base plate as a template and drill through the base fixing holes to the required depth of your concrete fixings. Ensure to use correct dust extraction techniques.
7. Fix the umbrella down using Dyna bolts or similar and cap with dome nuts.
8. Loosen the 1/2" grub screws and rotate umbrella to desired orientation. Lock grub screws again with Allen Key.
9. Locate the 8mm hole in the umbrella post 50mm up from the bottom of the post.
10. Using the 8mm cobalt drill bit, drill through the spigot from one side of the umbrella, then drill through the other side of the umbrella then run the drill through both holes.
11. Secure the umbrella to the spigot with the M8 x 90 mm bolt and Nylock nut.
12. Check Spigot bolts are tight.
13. Tighten the umbrella and remove the handle. Enjoy your UltraShade Heavy Duty Umbrella!

UltraShade

A.B.N. 77 010 472 563
56 Zillmere Rd, Boondall QLD 4034
P.O. Box 856, Virginia QLD 4014
Tel: (07) 3265 7288 Fax: (07) 3265 7304
Em: info@ultrashade.com.au



Heavy Duty Umbrella Installation Instructions

Bolt Down Installation – Fixing to Timber Deck:

Supplied Parts:	Recommended Fixings:	Tools and Hardware Required:
<ul style="list-style-type: none">a) The Base Plateb) Umbrella Spigotc) Five 3/8" x 1" Boltsd) Five 3/8" Spring Washerse) Two 1/2" Grub Screwsf) One 1/4" Allen Keyg) One M8 x 90 mm Stainless Bolt & Nylock Nuth) Umbrella Hati) Umbrella Handle	<p>M12 x 130mm Hex Head Bolts - Stainless Steel M12 x 150mm Head Bolts - Stainless Steel M12 Stainless Steel Nuts</p> <p>PPE Required: Dust mask, Safety Glasses, Hearing Protection, Gloves</p>	<ul style="list-style-type: none">1. M12 Long Series Drill Bit2. M5 Long Series Drill Bit,3. Cordless Drill4. Impact Driver5. Post Level6. Dust Extraction7. Spanner/Socket Set8. Tape Measure9. 8mm Cobalt Drill Bit10. 9/16" Spanner11. 1 box M12 S/S Flat Washer12. 75mm or 100mm Batten Screws13. Length of 75mm x 100mm hardwood.

1. Bolt the spigot to the base plate using the 3/8" x 1" bolts and spring washers supplied using the 9/16" spanner.
2. Locate the final position of the umbrella. It is ideal to have the base fit between two joists rather than sitting over the top of a joist.
3. With the base in its final position and orientation, use the base a template and drill through your decking boards through the base fixing holes with a M12 drill. This marks where you will need to reinforce the deck.
4. Get under the deck and measure the distance between you joists and cut two lengths of 75 x 100mm hardwood to those lengths.
5. Ensure the centre of the hardwood aligns with the holes drilled through the decking boards and pre-drill the joists and hardwood with a 5mm drill and fix to the joists using 75mm or 100mm batten screws.
6. From the top of the deck, drill through the hardwood reinforcing with the M12 drill bit.
7. Slide the spigot and the attached base up inside the umbrella post and lock in place using the Allen Key with the two supplied 1/2" Grub Screws.
8. Stand the umbrella in approximate location using 3 people. Have one person on the base end and two people on the canopy end, carry the umbrella to the approximate position and rest the base on the ground while two people hold the umbrella up. Have someone hold the base so it does not slip whilst two people push the umbrella vertical. Open the umbrella by removing the strap, attaching the handle and pushing all 8 arms out. Tighten the umbrella and lock open. Have a few people hold the umbrella and align the base to 12mm holes in the deck.
9. Using the post level, ensure the umbrella is plumb. Use M12 Stainless Steel Flat Washers under the fixing holes to level the base plate if required. The fixing bolts will be able to pass through the washers and hold the packing in place.
10. Insert the M12 Bolts into the base and through the holes in the deck and reinforcing hardwood.
11. From underneath the deck, fix the bolts down with a M12 washer and nut.
12. Loosen the 1/2" grub screws and rotate umbrella to desired orientation. Lock grub screws again with Allen Key.
13. Locate the 8mm hole in the umbrella post 50mm up from the bottom of the post.
14. Using the 8mm cobalt drill bit, drill through the spigot from one side of the umbrella, then drill through the other side of the umbrella then run the drill through both holes.
15. Secure the umbrella to the spigot with the M8 x 90 mm bolt and Nylock nut.
16. Check Spigot bolts are tight.
17. Tighten the umbrella and remove the handle. Enjoy your UltraShade Heavy Duty Umbrella!

UltraShade

A.B.N. 77 010 472 563
56 Zillmere Rd, Boondall QLD 4034
P.O. Box 856, Virginia QLD 4014
Tel: (07) 3265 7288 Fax: (07) 3265 7304
Em: info@ultrashade.com.au





Heavy Duty Umbrella Installation Instructions

In-ground Installations – Paving, soil or loose-ground


Supplied Parts:	Recommended Fixings:	Tools and Hardware Required:
<ul style="list-style-type: none">a) The In-ground Baseb) Umbrella Spigotc) Five 3/8" x 1" Boltsd) Five 3/8" Spring Washerse) Two 1/2" Grub Screwsf) One 1/4" Allen Keyg) One M8 x 90 mm Stainless Bolt & Nylock Nuth) Umbrella Hati) Umbrella Handle	<p>4 x 20 KG Bag Structural Concrete Premix (Rapid set is strongly discouraged)</p> <p>PPE Required: Dust mask, Safety Glasses, Hearing Protection, Gloves</p>	<ul style="list-style-type: none">1. Post Hole Shovel2. Spade3. Crowbar or Jackhammer4. Wheelbarrow5. Cordless Drill6. Post Level7. Hose8. Spanner/Socket Set9. Tape Measure10. 8mm Cobalt Drill Bit11. 9/16" Spanner

1. Bolt the Spigot to the In-ground base using the 3/8" x 1" Bolts and 3/8" Spring Washers and the 9/16" spanner.
2. Dig a hole for the concrete measuring approximately 400mm wide x 500mm deep. **Note:** The size of the hole depends on the soil type, (e.g., sandy soil = 500mm x 700mm). For taller umbrellas (custom height) = 500mm x 700mm.
3. Mix the required concrete and fill the hole until the level of the concrete is approximately 50mm below the ground level.
4. Insert the in-ground base into the concrete. The underside of the base flange should be **at least 12mm above** ground level.
5. Using a post level, ensure the spigot is plumb while the concrete goes off.
6. UltraShade recommend leaving the concrete for 5 – 7 days to cure.
7. Remove the spigot from the in-ground base and insert into umbrella pole and lock in place with the two 1/2" grub screws and Allen key.
8. Attach the Hat to the umbrella using the threaded hole at the top of the umbrella with the 9/16" Spanner. Once the Hat is attached, do not lay umbrella down as to not damage the hat.
9. Stand the umbrella using 3 people. Have one person on the base/spigot end and two people on the canopy end, carry the umbrella to the in-ground base and rest the flange of the spigot on the in-ground base. Have someone hold the spigot down so it does not slip whilst two people push the umbrella vertical. Align the spigot holes with the base holes and secure the umbrella with the 3/8" x 1" Bolts and spring washers. Open the umbrella by removing the strap, attaching the handle and pushing all 8 arms out. Tighten the umbrella and lock open.
10. Loosen the 1/2" grub screws and rotate umbrella to desired orientation. Lock grub screws again with Allen Key.
11. Locate the 8mm hole in the umbrella post 50mm up from the bottom of the post.
12. Using the 8mm cobalt drill bit, drill through the spigot from one side of the umbrella, then drill through the other side of the umbrella then run the drill through both holes.
13. Secure the umbrella to the spigot with the M8 x 90 mm bolt and Nylock nut.
14. Check the spigot bolts are tight.
15. Tighten the umbrella and remove the handle. Enjoy your UltraShade Heavy Duty Umbrella!


UltraShade




Timber Deck Side View



Timber Deck Plan View



Bolt Down Base on Concrete or Tiles



In-ground Base

Footing Size:
Approximately 400mm x 600 mm

UltraShade


A.B.N. 77 010 472 563

56 Zillmere Rd, Boondall QLD 4034

P.O. Box 856, Virginia QLD 4014

Tel: (07) 3265 7288 Fax: (07) 3265 7304

Em: info@ultrashade.com.au




LOCKING BOLT INSTALLATION INFORMATION

To ensure the umbrella remains secure and does not turn or lift off the spigot, locate the 8mm holes in the umbrella post, 50mm from the bottom. Then use an 8mm drill bit to drill through the umbrella post then through the spigot. Drill through one side of the post, then drill through the opposite side, then pass the drill bit through both holes to ensure a bolt can pass through.


Once the holes have been drilled, secure the umbrella to the spigot by passing the supplied M8 x 90mm Bolt through the drilled holes and secure it with the provided M8 Nut using two 13mm Spanners.

NB: If this precaution is not taken when first installing the umbrella it could cause damage or injury due to turning or lifting off the spigot.



UltraShade

A.B.N. 77 010 472 563
56 Zillmere Rd, Boondall QLD 4034
P.O. Box 856, Virginia QLD 4014
Tel: (07) 3265 7288 Fax: (07) 3265 7304
Em: info@ultrashade.com.au



How to Open and Close Your UltraShade Heavy Duty Umbrella

To Open:

1. While lightly holding one arm out as far as possible, gently push all of the remaining 7 umbrella arms out from the main post.
2. The umbrella should unfold mostly by itself. If it fails to open, at least one of the arms will be in the over locked position.
3. Bolt the handle to the round stainless-steel axle and wind it up.
4. Open the umbrella until the canopy is taut.
5. Secure the umbrella by placing the locking pin into the round stainless-steel axle and into the post.
6. Store the handle in a safe place.
7. Ensure that the canopy is taut to prevent damage from stress fracturing due to flapping.

To Close:

1. Attach the handle to the round stainless-steel axle.
2. Release the pressure on the locking pin by using your body weight to turn the umbrella in a clock-wise direction.
3. Remove the locking pin from the axle and main post.
4. Wind the umbrella down with the handle in an anti-clockwise direction.
5. Ensure that all the canopy material is not jammed between the arms and arm brackets or between the arms and the bottom bracket system, and push the arms toward the main post. Failure to remove the fabric from the pinch points will result in damage to the canopy and will not be covered under warranty.
6. Wrap all the canopy material around the umbrella in the same way you would for a handheld rain umbrella.
7. Secure it with the provided strap.
8. Remove and store the handle in a safe place.


Note: It's important to secure the panels with the strap provided to prevent damage to the canopy, which is not covered by our warranty. If the umbrella is left in the down position for more than 24 hours, wind may cause flapping of the panels, which could result in fabric stress fracturing. This damage is not covered by warranty.

You can find an instructional video at:

www.youtube.com/ultrashadeumbrellas

UltraShade

A.B.N. 77 010 472 563
56 Zillmere Rd, Boondall QLD 4034
P.O. Box 856, Virginia QLD 4014
Tel: (07) 3265 7288 Fax: (07) 3265 7304
Em: info@ultrashade.com.au



FABRIC CARE INSTRUCTIONS

Congratulations on your new umbrella! To prolong the life of your umbrella canopy, it is important to care for it properly. Regular cleaning and re treatment of the fabric will keep it looking great and extend its life. Here are some tips for caring for canvas and acrylic fabrics:

For new canvas installations, erect the umbrella fully and leave it erected for at least 2 to 4 days to allow the canvas to condition.

Ensure the canopy is thoroughly dry before closing it away to avoid encouraging algae, mildew, or other fungal growth.

Brush the fabric regularly with a soft brush and hose it down occasionally with clear, cold water to remove dust and grime. Do not let dirt, dust, grime, leaf litter, or bird matter remain on the fabric.

Cleaning Acrylic Fabrics:

Brush off any loose dirt and hose down the fabric.

Clean the fabric with a mild soap in lukewarm water (37°C). Rinse thoroughly and do not use detergents.

For more stubborn stains, soak the fabric for approximately 20 minutes in a solution of no more than 1/2 cup of non-chlorine bleach and 1/4 cup natural soap per 4 liters of water at approximately 30-35°C. Rinse thoroughly in cold water to remove all the soap.

Allow the fabric to air dry and apply an air-curing re-treatment to restore water repellent.

To aid in the care of your fabric awnings and blinds, we recommend using Brellaguard 303 Fabric Cleaner for acrylic fabrics. For restoring water repellent to acrylic fabric products, use 303 Fabric Guard Water Repellent for all woven fabrics.

To clean PVC fabrics, used in some outdoor umbrellas, follow these steps:

Remove any loose dirt or debris from the fabric surface using a soft brush or a dry cloth.

Prepare a cleaning solution by mixing warm water with a mild detergent. Use a non-abrasive and non-solvent cleaner.

Apply the cleaning solution to the fabric surface using a soft brush or sponge, working in a circular motion. Avoid using abrasive brushes or pads, as these can damage the fabric.

Rinse the fabric thoroughly with clean water, using a garden hose or a bucket of clean water.


Wipe off excess water from the fabric using a dry cloth, and allow the fabric to air dry completely before storing or using again.

For stubborn stains or marks, you may need to use a specialized cleaner recommended by the manufacturer. Be sure to follow the instructions carefully and test the cleaner on a small, inconspicuous area of the fabric first to ensure that it doesn't cause damage or discoloration.

If you have any questions about caring for your umbrella canopy, speak with one of our friendly customer service staff.

UltraShade

A.B.N. 77 010 472 563
56 Zillmere Rd, Boondall QLD 4034
P.O. Box 856, Virginia QLD 4014
Tel: (07) 3265 7288 Fax: (07) 3265 7304
Em: info@ultrashade.com.au



HEAVY DUTY UMBRELLA WARRANTY

Aluminum Frames are covered by a 5 Year structural warranty. Warranty specifically excludes damage to the powder coat finish caused by corrosion, scratching, pitting, fading or peeling.

Canopy Fabrics are covered by a 3 Year manufactures and workmanship warranty. Warranty specifically excludes; stains, mildew and fading.

Conditions of Warranty:

1. This warranty does not cover any repairs consequent upon accident, alterations or repairs by any other than an authorised dealer/agent of UltraShade, misuse, fire, floods, earthquakes or excessively high wind conditions.
2. This warranty applies to the original purchaser from the purchase date and covers manufacturing faults and defects.
3. This warranty is valid only for installation made by UltraShade/ Agent/ Dealer/Yourself/ Tradesman: The installation must be carried out exactly as shown in the Ultrashade Installation Instructions and Technical Information.
4. Owner to ascertain position of all underground pipes and electrical wires and notify installer of any obstacles. Although all care will be taken, no responsibility can be accepted for any underground breakages.
5. This warranty is only valid if the Locking pin is installed correctly and both pin and strap are used correctly at all times whilst the umbrella is erected and collapsed. Umbrella should not be closed for more than a 24 hour period.
6. This warranty is valid only if the canopy has been kept clean and free of dust/debris with regular hosing as this will help prolong the life of the canopy.
7. This warranty is only valid if the umbrella is put up and collapsed as detailed in the Technical information.
8. The cost of transportation and insurance both ways for any repair to the UltraShade Umbrella is to be paid by the claimant.
9. Warranty specifically excludes general wear and tear, rusting of steel components and parts, corrosion and damage caused as a result of failure to observe reasonable care, maintenance and assembly instructions.
10. UltraShade reserves the right to determine whether or not fault is caused by faulty workmanship or material or any other part is defective.
11. UltraShade may offer advice but accepts no responsibility to the suitability of the ultimate position of the UltraShade Umbrellas.

The benefits conferred by this manufacturer's warranty are in addition to all rights and remedies conveyed by the Competition and Consumer Act 2010 (Commonwealth), and any other statutory rights to which you may already be entitled, and this warranty does not exclude, restrict or modify any such rights or remedies that are implied by law.